

EZStation Video Management Software



Key Features

- Unified management for IP cameras, DVRs, NVRs, storage servers, stream servers, video wall controllers, and etc.
- Flexible to manage up to 256 local channels and 128 cloud channels; add, edit and share cloud devices.
- Automatic device search (or search by segment); add devices by domain name/IP address; add devices and adjust time in batch.
- Diverse capabilities:
 - Live view: up to 36 live view, view resume, custom view, split screen, multi-window display, corridor mode, sequence display, video-associated audio, two-way audio and audio broadcast
 - Record: local recording, recording schedule, alarm record, record download
 - Playback: time/event retrieval, local/remote playback, async/sync playback, VOD for different speed, smart search and SD card search
 - PTZ control: Pan, tilt, zoom, 3D positioning, preset, patrol, pattern, and patrol plan
 - Alarm: temperature, device online/offline, motion detection, and VCA alarming and alarm triggering for live view, recording
 - People counting: entered/left/entered and left statistics, daily/weekly/monthly/yearly report export.
 - E-Map: hot spot for easy live view, hot region for sub-map, eagle eye, and map alarming
 - Video wall: decoding channel configuration, channel preview, sequence display and playback on Video wall

- Cost-effective EZRecorder(software) for storage server and cost-effective EZStreamer(software) for stream server
- Flexible maintenance such as log export, alarm info export
- Friendly user interface for easy operation

Specifications

Version	EZStation_1102-B0038(IN)
Function	Description
Device Management	
Devices Supported	Max. 256 local channels and 128 cloud channels
	Max. 256 local encoding devices and 128 cloud devices
	Max. 32 decoding devices
	Max. 8 EZRecorder storage servers
	Max. 4 EZStreamer stream servers
Features	Auto device discovery, and adding, configuring, time adjusting in batch
Live Monitoring	
Screen Layout	1/ 4/ 5 /6 /8 /9 /10 /13 /16 /17 /25 /32 /36 split screen(s) with up to 1 sub screen Note: Max. 36 screens live view
PTZ Control	Pan, Tilt, Zoom, Preset, Patrol, 3D positioning, IR control, wiper control, heat control, snow removing Note: To realize functionality above, please refer to the product's practical capacity.
Features	Sequence display, snapshot, local record, audio, two-way talk, and instant playback
Playback	
Video Source	Recording video from DVR/NVR and EZRecorder
Max Channels	16 (Async)/16 (Sync)
Search Type	Time/event/calendar
Export File	.ts, .mp4
Features	Recording schedule and download, snapshot, -16x~16x speed for forward and backward, audio, digital zoom
Alarm	
Type	Service alarms and device alarms
Alarm Triggering	Live view, recording, email, preset, alarm output and etc.
Features	Alarm schedule, actions setup, alarm memo, alarm info popup
E-Map	
Format	PNG/JPEG/BMP
Map Alarm	Alarm flash, search and acknowledge
Features	Hot spot, hot region, map zoom in/out, map group, eagle eye
System Requirement	
Operating System	Microsoft Windows7/Windows8 (32-bit or 64-bit) Note: EZ Software only supports 64-bit system compatible with 32-bit.
CPU	Intel Pentium IV 3.0 GHZ or higher (4Cores,3.0GHZ are recommended)
Memory	1GB or higher
Network Card	Gigabit Ethernet network card (or higher) are recommended
Display Resolution	1024*768 or higher (EZStation)

HDD	1TB or higher (EZRecorder)
-----	----------------------------

Zhejiang Uniview Technologies Co., Ltd.

South Tower, Building 10, Wanlun Science Park, 88 Jiangling Road, Hangzhou, P.R. China 310051

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2011-2016 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.