

UTP Category 6 Cables

Content of Data Sheet				
Product model	CAB-LC6-BU			
Product specification	Quality verified by latest standard AS/CA S008:2020			
Test Standard	ISO/IEC11801、TIA-568-C.2			
Conductor	Material	Solid-Bare Copper		
	AWG	24		
	Nom.O.D.(mm)	0.52±0.03 mm		
	DC resistance	≤95 Ω/km		
Insulation	Material	HDPE		
	Thickness	0.2±0.02 mm		
	Diameter	0.93±0.05 mm		
	Color			Blue/White- Blue
		Orange/White-Orange	Brown/White-Brown	
Pitch	Offset pitch	≤20 mm		
	Cable pitch	≤120 mm		
Sheath	Material	PVC(complies RoHS/REACH)		
	External O.D.	5.8±0.3 mm		
	Color	Blue		
	Tensile strength	>13.5 Mpa		
	Thickness	0.6±0.05 mm		
Surface Printing	Letter height	3.0±0.3 mm		
	Color	Black		
	Print error & Space	1±0.005 m		
	Case number	Yes		
Packing	Packing	Carton + Plastic shaft		

	Once packing dimension	331mm*255mm*338mm		
	Twice packing dimension	550mm*350mm*360mm		
	Twice packing quantity	2 cases		
Packing length	305±1m			
Rip-cord	Yes	Crossing backbone	Yes	
Ambient temperature	-20°C ~ 60°C			

Zhejiang Uniview Technologies Co.,Ltd.

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2011-2018 Zhejiang Uniview Technologies Co.,Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.